

HI-450PG

File Number: E65424

Yellow Card® 

COMPANY

KOREA KUMHO PETROCHEMICAL CO LTD

EAST WING 10-14F
SIGNATURE TOWERS SEOUL
100 CHEONGGYECHEON-RO JUNG-GU
SEOUL, 100-230 Republic of Korea

MODEL INFO

HI-450PG

Polystyrene (PS), furnished as pellets

FLAMMABILITY PROPERTIES	VALUE	TEST METHOD
Flammability		ANSI/UL 94
1.5 mm, Color: ALL	HB	
3.0 mm, Color: ALL	HB	
ISO/IEC FLAMMABILITY PROPERTIES	VALUE	TEST METHOD
Flammability		IEC 60695-11-10
1.5 mm, Color: ALL	HB75	
3.0 mm, Color: ALL	HB40	
ELECTRICAL PROPERTIES	VALUE	TEST METHOD
Hot-wire Ignition (HWI)		UL 746A
1.5 mm	PLC 3	
3.0 mm	PLC 3	
High Amp Arc Ignition (HAI)		UL 746A
1.5 mm	PLC 1	

Feedback

3.0 mm	PLC 1	
Comparative Tracking Index (CTI)	PLC 1	UL 746A
Dielectric Strength	35 kV/mm	ASTM D149
High Voltage Arc Tracking Rate (HVTR)	PLC 4	
Volume Resistivity	1.0E+16 ohms-cm	ASTM D257/IEC 60093
High Voltage, Low Current Arc Resistance	PLC 5	
THERMAL PROPERTIES	VALUE	TEST METHOD
Relative Thermal Index - Electrical Strength		UL 746B
1.5 mm	50 °C	
3.0 mm	50 °C	
Relative Thermal Index - Mechanical Impact		UL 746B
1.5 mm	50 °C	
3.0 mm	50 °C	
Relative Thermal Index - Mechanical Strength		UL 746B
1.5 mm	50 °C	
3.0 mm	50 °C	
PHYSICAL PROPERTIES	VALUE	TEST METHOD
Dimensional Change	0.0 %	ASTM D1042/ISO 2796

Report Date: 1989-04-06
Revision Date: 2019-05-02

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."

Feedback