

## KNB 40H

### Product Introduction

- KUMHO KNB is a cold emulsion copolymer of acrylonitrile and butadiene.
- It has excellent resistance to hydrocarbon solvents, vegetable oils, alkalis, and many other liquids and gases.
- Resistance to abrasion, heat, water, and flexing are also provided by our NBR.

### Product Properties

Property	Typical value	Test Method
Volatile Matter (wt.%)	max. 0.5	ASTM D5668
Ash Content (wt.%)	max. 0.8	ASTM D5667
Bound AN (wt.%)	39.0~43.0	UPS E493-03-U32
Raw Mooney(ML1+4,100℃)	73~87	ASTM D1646
300% Modulus (kgf/cm <sup>2</sup> )	130~190	ASTM D412
Tensile strength (kgf/cm <sup>2</sup> )	Min. 220	
Elongation (%)	Min. 400	

### Characteristics and Applications

- Typical application is for industrial goods like fuel hose, gasket and seal
- Compatible with carbon black, making it widely used for industrial good having oil-resistance

### Manufacturer location

- Ulsan in Republic of KOREA

### Product safety

- Relevant safety data and references can be found in the safety data sheet.

### Shelf life/Condition

- 1 year from the production date at temperature not exceeding 35 °C, keeping away from direct sunlight

### Packaging

- Bale weight : 35kg (Wrapped by polyethylene film)
- Box weight : 1,050kg (30 Bales)

**Head Office (Sales)**  
Signature tower, East-wing 11F  
100, Cheonggyecheon-ro, Jung-gu, Seoul, Korea  
Tel. +82-2-6961-1600 Fax. +82-2-6961-1619  
www.kkpc.com

**Research Center (Technical Service)**  
1557, Yuseongdae-ro, Yuseong-Gu, Daejeon, KOREA  
Tel. +82-42-865-8600 Fax. +82-42-862-5651

**Quality Assurance (Ulsan Rubber Plant)**  
64, Sanggae-ro, Nam-gu, Ulsan, Korea  
Tel. 82-52-259-6114 Fax. 82-52-275-6547